







1.7 Software Features For All Camera Modules

 M12  S14M  D14  M24M  D24M  Q24M	Basic Model	Web Model	IT Model	Secure Model
Software Features For All Camera Modules				
Digital zoom (continuous) with panning:	only Q24	X	X	X
Motion JPEG/MxPEG video streaming	X/X	X/X	X/X	X/X
Custom exposure windows	X	X	X	X
Video motion detection	X	X	X	X
Time and event control (FTP, e-mail, logos)	X	X	X	X
Weekly schedules/holidays	-	X	X	X
Web functionality (FTP, e-mail)	X	X	X	X
Quad/MultiView in browser	X	X	X	X
Recording/Playback in browser	X	X	X	X
Logo generator, animated	-	X	X	X
Snapshot recording (pre- and post-alarm images)	3	3	10	50
Terabyte ring buffer (Win/Lin/Mac) via network	-	-	X	X
Continuous video/sound recording, 0.2 to 30 fps	-	-	X	X
Video/audio recording (event-controlled)	-	-	X	X
Event-controlled frame rate with continuous audio	-	-	X	X
Flexible event logic	-	-	-	X
Master/slave arming by one camera	-	-	-	X
Time-scheduled privacy zones, several areas	-	-	-	X
Bidirectional sound (IP) from/to browser	-	-	X ⁵	X ⁵
Customized voice messages	-	-	X	X
VoIP telephony (audio/video, SIP)	-	-	X ⁵	X ⁵
Alarm calls to softphones (SIP), for example, X-Lite	-	-	X	X
Remote alarm notification (alarm via network message)	-	-	X	X
RS232 Data Logger/Terminal ⁶	-	-	X	X
Programming interface/HTTP API	-	-	X	X
Security features (HTTPS/SSL, IP-level access control, network authentication IEEE 802.1X)	X	X	X	X
MxAnalytics (image analysis functions)	-	-	-	X*
Model Feature List				
Image size	VGA	3MEGA	VGA	3MEGA
Image sensor	Color	Color	Color & B/W	Color & B/W
Audio support (microphone/loudspeaker)	-/L ⁵	-/L ⁵	M/L ⁵	M/L ⁵

New in S14:
Echo elimination, any number of action profiles can be executed simultaneously per event, full image storage

⁵ An external speaker and microphone can be connected directly on the S14

⁶ S14 if using MX-232-IO-Box

*Currently available for Q24M-SEC only